

Service interface kit, Pact series circuit breakers

LV485500

Main

Product or component type	Testing kit	
accessory / separate part category	Maintenance accessory	
Range compatibility	Masterpact MasterPact NT Masterpact MasterPact NW EasyPact EasyPact MVS ComPact ComPact NS630b1600 ComPact ComPact NS1600b3200	
Provided equipment	1 power supply 1 USB cable 3 test cables	
[Ue] rated operational voltage	115/230 V AC +/- 10 % 4763 Hz	
Trip time measurement	07500 s +/- 0.1 %	

Complementary

[Uimp] rated impulse withstand voltage	12 kV
IP degree of protection	IP20
Height	106 mm
Width	451 mm
Depth	358 mm
Net weight	2.8 kg
product certifications	CE UL
Standards	IEC 61010-1 IEC 61010-2-030 UL 61010-1 CSA C22.2 No 61010-1 EN 60068-2-32

Environment

Overvoltage category		
Electromagnetic compatibility	Conducted RF disturbances conforming to EN 55011 Emission tests conforming to EN 55032 Immunity for industrial environments conforming to IEC 61000-6-2 Emission standard for industrial environments conforming to IEC 61000-6-4 Limits for harmonic current emissions conforming to IEC 61000-3-2 Limitation of voltage changes, voltage fluctuations and flicker in low-voltage conforming to IEC 61000-3-3	
Ambient air temperature for operation	-1055 °C	
Ambient air temperature for storage	-4085 °C	

Relative humidity 5...95 % at 55 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.5 cm
Package 1 Width	38.0 cm
Package 1 Length	47.0 cm
Package 1 Weight	4.66 kg



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information